<u>**SPECIFICATION**</u>

5 <u>**CONTAINER INSPECTION MACHINE**</u>

The present invention relates to machines which have a camera based inspection system for inspecting bottles for defects.

10

<u>**BACKGROUND OF THE INVENTION**</u>

Machines for inspecting glass bottles conduct a great variety of inspections. More and more of 15 these inspections are conducted using camera technology and often the light source is made up of a L.E.D. matrix. Conventionally the intensity of a vertical row is varied relative to the intensity of neighboring rows to achieve sinusoidal or triangular 20 intensity patterns which facilitate the identification of defects.

<u>**OBJECT OF THE INVENTION**</u>

25 It is an object of the present invention to provide a system for inspecting glass containers using such a L.E.D. matrix and to be able to define bottle height with the matrix.

Other objects and advantages of the present 30 invention will become apparent from the following portion of this specification and from the accompanying drawings which illustrate, in accordance with the mandate of the patent statutes, a presently preferred embodiment incorporating the 35 principles of the invention.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic illustration showing a bottle supported by a conveyor at an inspection station where it is illuminated by a light matrix and the image is evaluated by a camera system;

Figure 2 is a schematic diagram for a temperature correction circuit for the voltage applied in figure 1; and

Figure 3 is view similar to that of Figure 1 showing a triangulated periodic intensity pattern.

## BRIEF DESCRIPTION OF THE PREFERRED EMBODIMENT

Figure 1 shows a bottle 10 supported by a conveyor 12 at an inspection station. A light source 14 in the form of a rectangular or square L.E.D. matrix directs light horizontally through the bottle and the bottle is imaged on a suitable camera 16 and this image is evaluated by a processor 18. The light source is schematically represented by a single vertical row of L.E.D.'s, whereas there would in fact be numerous vertical rows. In Figure 1, the intensity of all the L.E.D's is the same as represented by equal length intensity arrows 20. The intensity of each L.E.D. defining the light source 14 is controlled by the processor.

To the right of the top of the bottle in figure 1 are intensity arrows which are representative of the intensity of light imaged on the camera in this area. Above the top of the bottle the light

intensity would be equal to the intensity of the light emitted from the light source and down from the top of the bottle, as shown by the shorter intensity arrows light transmitted to the camera would be of a much lower intensity.

The control algorithm is shown in Figure 2. The processor first proceeds, during a setup mode, to Define The Intensity Of Each L.E.D. In The Center Row Of L.E.D.'s Full Intensity 22 (the processor would know which vertical row was the central row since the location of the bottle at the inspection station is located directly or indirectly via a sensor and the center row could be one or more vertical rows). To determine the height of the bottle, the processor would then Sequentially Operate Banks of L.E.D.'s Upwardly From The Bottom Of The Bottle 24 (a bank might, for example, be four vertically spaced L.E.D.'s). In this illustration, the lowest bank would be operated at full intensity, then the bank vertically above, etc. The intensity gradient of the imaged light of each bank is evaluated. When the operated bank intersects the top of the bottle the processor will answer the inquiry "Is There An Intensity Transition Along The Bank Indicative Of The Top Of The Bottle?" 26 in the affirmative and will then Define The L.E.D. That Locates The Top Of The Bottle 28. For purposes of illustration, the arrow representing light from the L.E.D. that locates the top of the bottle is indexed 38.

To inspect a bottle a periodically varying light intensity is defined. The intensity of each L.E.D. in a horizontal row will be uniform but the intensity of the horizontal rows will vary. Varying intensity per a sinusoidal curve which in the ideal is a triangulated form enables the identification of

defects in the sidewall of the bottle.   Figure 3
illustrates a periodically repeating triangulated
intensity gradient 40 for a vertical row of L.E.D.s.
The vertical period from one peak to the next peak
5   (or from one low to the next low) corresponds to a
selected number of horizontally extending L.E.D.
rows (14 for example).   In the disclosed embodiment
the intensity varies between full intensity and a
low intensity every 14 L.E.D.'s but it could also
10   vary between full intensity and black.   It should be
noted that to achieve the triangulated intensity
pattern shown, the intensity of individual rows of
L.E.D.'s will have to be adjusted and these L.E.D.
settings will be stored in memory so that the
15   processor can establish this triangulated intensity
pattern.

Referring again to Figure 2, the processor then
proceeds to Define A Periodic Intensity Pattern 30
and then to Vertically Shift The Periodic Intensity
20   Pattern To Locate The L.E.D. That Locates The Top Of
The Bottle At A Peak On The Periodic Intensity
Pattern 32 (arrow 38 represents light from the
L.E.D. that locates the top of the bottle).